



FOR BRAND PRODUCTS (AJA / ATMOS SHOGUN / Roland)

FOR AJA PRODUCTS




CABLE-AJA1
AJA DC cable
length : 50cm

CONNECTOR-AJA1
only connector for AJA




PV-AJA-DC1
for mini converter
(please select model●)
5V : output fix 5V
12V : output fix 12V
max 10W
output connector: **AJA connector**
input voltage: DC11~17V
H140×W90×D20mm Weight260g




PV-AJA-DCTHROUGH1
for mini converter
(can use 5~18V AJA products)


output voltage: **THROUGH(12.8~16.8V)**
output connector: **AJA connector**
input voltage: DC11~17V
H140×W90×D20mm Weight200g




PDV(AJA)-DC1
for mini converter
(please select model●)
S : for SONY(L/M) P: for Panasonic VBD
SV : for SONY(V) C: Canon BP970/BP828
(please select model■)
5V : output 5V 12V : output 12V
max 10W
output connector: **AJA connector**
input voltage: DC6~8.4V
H90×W48×D20mm Weight60g




PV-AJA-BOX-DC1
for mini converter
V plate with BOX
(please select model●)
5V : output 5V 12V : output 12V
(please select model■)
12060 : 117*61*25mm
15080 : 147*79*25mm
input voltage: DC11~17V
H140×W90×D40mm
Weight400g




SGPS-AJA-BOX-DC1
you can [mount&work] camera
with receive V mount & battery side V mount
(please select model●)
5V : output 5V 12V : output 12V
(please select model■)
12060 : 117*61*25mm 15080 : 147*79*25mm
output 1 : **12V10W(AJA cable)**
output 2 : **THROUGH voltage(Vmount)**
input voltage: DC11~17V
H140×W90×D65mm Weight670g




PTAP-AJA-DC1
POWERTAP→AJA PLUG
(THROUGH voltage)
(can use 5~18V AJA)
output voltage: **THROUGH**
(12.8~16.8V)
output connector **AJA connector**
input connector: **POWERTAP**



XP-PTAP(M)-AJA-DC1
POWERTAP→AJA PLUG
(output: follow ●V fix)
(please select model●)
5V : output 5V 12V : 12V
max20W
output connector **AJA connector**
input voltage: DC11~17V
input connector: **POWERTAP**



XP-XLR4P(M)-AJA-DC1
XLR4P(M)→AJA PLUG
(output: follow ●V fix)
(please select model●)
5V : output 5V 12V : 12V
max20W
output connector **AJA connector**
input voltage: DC11~17V
input connector: **XLR4P(M)**



XP-DCJACK-AJA-DC1
DC jack→AJA PLUG
(output: follow ●V fix)
(please select model●)
5V : output 5V 12V : 12V
max20W
output connector **AJA connector**
input voltage: DC11~17V
input connector: **2.1Φ DC jack center(-)minus**

FOR ATMOS SHOGUN PRODUCTS

set PV-TS-SHOGUN-S
for **SHOGUN SIDE** mount
you can mount SHOGUN rear ENG Camera
1pcs*V mount battery can work SHOGUN and ENG camera



monitoring cameraman side



you can mount both side

set PV-TS-SHOGUN-B
for **SHOGUN BACK** mount
you can mount SHOGUN rear ENG Camera
1pcs*V mount battery can work SHOGUN and Camera




C-16A
Camera shoe for SHOGUN
SLIDE TYPE
max load 4kg
H89×W66×D44mm
Weight 152g




C-17A
SCREW TYPE
max load 4kg

PTAP-6
Cable for SHOGUN
POWERTAP-POWERTAP
length : 70cm

FOR Roland PRODUCTS



PV-BP
for VC-1 converter
output voltage: **THROUGH**
(12.8~16.8V)
output connector:
VC-1 connector 2.1Φ center(-)
H140×W90×D20mm
Weight200g




PDV(BP)
for VC-1 converter
output voltage: **THROUGH**
(DC6~8.4V)
output connector:
VC-1 connector 2.1Φ center(-)
H90×W45×D18mm 100g
(please select model)
F : for SONY(L) U : SONY(BPU) P: Panasonic VBD I: JVC SSL
B: Panasonic VBG E: Canon LPE6 C: Canon BP970G




PV-NCLAMP-1
V Plate with mini clamp
open width 13~35mm, max load 4kg
you can fit tripod and stand
H140×W90×D45mm 280g
PV-NCLAMP-1-BP
PV-NCLAMP-1+PTAP-4 set



PV-XLR4P
for **R-8**
output voltage: **THROUGH**
(12.8~16.8V)
output connector: **XLR4P(F)**
H140×W90×D20mm
Weight240g



PV-ROLANDVC1-BOX
for VC-1 converter
V plate with BOX
output voltage: **THROUGH**
(12.8~16.8V)
output connector:
VC-1 connector 2.1Φ center(-)
H60×W140×D140mm 660g



PTAP-4
POWERTAP→VC-1 PLUG
cable length : 26cm

XLR4P(M)-BP
XLR4P(M)→VC-1 PLUG
cable length : 26cm

FOR BRAND PRODUCTS (Blackmagic / Panasonic HMR10)


FOR Blackmagic Design PRODUCTS



PV-BLA-DC1
for 12V mini converter
output voltage : fix 1 2 V
max 1 0W
output connector: BLA DCplug
input voltage:DC11~17V
H140×W90×D20mm 260g



PV-BLA-DCTHROUGH1
for CinemaCamera etc.
output voltage:THROUGH
(12.8~16.8V)
output connector: BLA DCplug
H140×W90×D20mm 200g




CHEP-1
CHEESE PLATE
for V mount
H153×W88×D5.5mm 200g



PDV(O)-BLA-DC1
for 12V mini converter
(please select model●)
S: for SONY(L/M) P: for Panasonic VBD
SV: for SONY(V) C:Canon BP970/BP828
output voltage: fix 1 2 V
max 1 0W
output connector: BLA DCplug
input voltage: DC6~8.4V
H90×W48×D120mm 60g



PDVW(O)-BLA-DCTHROUGH1
for CinemaCamera etc.
(please select model●)
F: for SONY(L) U: SONY(BPU)
P:Panasonic VBD I:JVC SSL
B:Panasonic VBG E:Canon LPE6
C:Canon BP970G
output voltage:THROUGH
(12.8~16.8V)
output connector: BLA DCplug
input voltage: DC6~8.4V × 2
H95×W95×D20mm 190g



CHEP-PDVW1
CHEESE PLATE
for PDVW(O)
H78×W88×D6.5mm 100g



PTAP-BLA-DC1
POWERTAP→
BLA DCplug
(THROUGH voltage)
output voltage:THROUGH
(12.8~16.8V)
output connector BLA DCplug
input connector:POWERTAP



XP-PTAP(M)-BLA-DC1
POWERTAP→
BLA DCplug (fix12V)
max load 20W
output voltage: 1 2 V
output connector BLA DCplug
input voltage:DC11~17V
input connector:POWERTAP



XP-XLR4P(M)-BLA-DC1
X L R 4 P (M)→
BLA DCplug (fix12V)
max load 20W
output voltage: 1 2 V
output connector BLA DCplug
input voltage:DC11~17V
input connector: X L R 4 P (M)



XP-DCJACK-BLA-DC1
DC jack→
BLA DCplug (fix12V)
max load 20W
output voltage: 1 2 V
output CONNE BLA DCplug
input voltage:DC11~17V
input CONNE2.1DC jack
center(-)minus



PV-BLABOX-DC1
for mini converter
(H120*28*92.15mm)
V plate with BOX
output voltage: fix 1 2 V
max 1 0W
output connector: BLA DCplug
input voltage:DC11~17V
H140×W90×D45mm 490g



SGPS-BLABOX-DC1
can [mount & work] camera
with receive & battery side V mount
output 1 :12V10W(BLA cable)
output 2 :THROUGH (Vmount)
input voltage:DC11~17V
H140×W90×D65mm
Weight 670g



PV-BLAHDBOX-DC1
for Heavy Duty converter
V plate with BOX
H140×W118×D50mm
Weight470g
SGPS-BLAHDBOX-DC1
you can
[mount & work] camera
H140×W118×D70mm
Weight 620g



FOR Panasonic HMR-10(POVCAM) PRODUCTS

set PV-TS-7.3-HMR10

for POVCAM(HMR10) SIDE mount
you can mount HMR10 rear ENG Camera
1pcs*V mount battery can work
HMR10 and ENG camera



monitoring cameraman side



you can mount both side

PV-HMR10

for POVCAM(HMR10)
mount V plate



P-HMR10-SHOE

POVCAM(HMR10)
mount plate for camera shoe
can fit Vertical•Horizontal



XP-DV-HMR10
for Panasonic AG-HMR10
(and VBG series)
input Voltage :DC11~17V
Output Volatage :DC7.3V



set XP-DV-HMR10-PV
Vplate set
BTK-S+XP-DV-HMR



set GPS-7.3-HMR10
HMR10 mount back of V mount
GPS-7.3-HMR10+
XP-DV-HMR10

1
PROFILE
SUITABLE
SHEET

2
BATTERY
PLATE

3
FOR BRAND
PRODUCTS

4
CABLE
CONNECTOR

5
RAINCOVER
and more

6
SOFT BAG

7
SHOE
CLIP•POLE
and more

8
OTHER