

CLIP

G-3A

MAX 4 kg pinch width: 50 mm



H115×W115×D63 Weight 360g

G-2

MAX1~2kg



pinch width:50mm
H105×W115×D63mm
Weight 307g

G-2 GRIP

MAX1~2kg



pinch width:50mm
H225×W155×D65mm
Weight 528g

G-4A

MAX 6 kg



pinch width:50mm
H135×W115×D63mm
Weight 476g

G-3-CLIPNOMI

only CLIP part
top : 1/4(M) screw



OTHER

1
PROFILE
SUITABLE
SHEET

2
BATTERY
PLATE

3
FOR BRAND
PRODUCTS

4
CABLE
CONNECTOR

5
RAINCOVER
and more

6
SOFT BAG

7
SHOE
CLIP•POLE
and more

8
OTHER

LENS CLEANING

FCLOTH-1

Silicon Cloth
for LENS and EQUIPMENT



AG+WETLENSCP-1015

WET type cleaning paper with AG+



AG + ...AG+ is silver ion.
AG+ effect
•Antibacterial
•Antifungal
•Sterilization

maintenance of LENS and Camera.
monitor / smart phone / glasses etc.

• (1 piece)
AG+WETLENSCP-1015
• SET (50piece)
AG+WETLENSCP-1015-50SET



LENSCP-1017-30

dry type cleaning paper



paper size:100×170mm


• (30piece)
LENSCP-1017-30

• SET (30piece×10)
LENSCP-1017-30-10SET

ELECTRICAL CONTACT CLEANER

NANO CARBON PEN

Nano-sized particles fill the irregularities of the metal.
It does not attack the metal.
you can maintenance by yourself!!



CONTACT POINT

• lens mount
• battery terminal
• media(SD/CF etc.)
• earphone
• HANDY PHONE etc.



FLASH METER with Color LCD

POLARIS K a r a t

FD function is <World's first>

Contrast Function

ΔEV

Useful for checking lighting evenness of backgrounds, and lighting ratio.

Flash Duration Mode

FD

Measuring the duration time of the strobe flash. (T0.5: 1/100~1/9000)

Flash Ratio Function

FR

On Flash measuring, ratio of strobe light of overall light quantity is displayed. (in 1% increment)

Auto ISO Mode

ISO

Setting desired Aperture (F) and Shutter Speed (T) find appropriate ISO number.

